

LP58

Thermal Barcode Printer

- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Support QR CODE Printing

ACTIVA



Coffee Shop



Shopping




Mart



LP58

Thermal Barcode Printer



Model XP-237B		
Mode	Label print mode	Receipt print mode
Printing Features		
Resolution	203 DPI	
Printing method	Direct Thermal	
Max.print speed	50.8~101 mm/s Max.	90 mm/s Max.
Max.print width	48 mm	48mm
Max.print length	Max. 105 mm	/
Media		
Media type	Paper End, Cover Open, Gap	Paper End, Cover Open
Media width	20~60 mm	58mm
Media thickness	0.06 ~ 0.08 mm	
Media roll diameter	Max.80 mm	
Supply method	Easy Paper Loading	
Performance Features		
NV flash	576 Kbytes	576 Kbytes
Interfaces	USB/USB+Lan/USB+Bluetooth	
Sensors	Paper End, Cover Open, Gap	Paper End, Cover Open
Drawer port	1 ports (Pin 2 for cashdrawer)	
Fonts/Graphics/Symbologies		
Character sizes	Font 0 to Font8	Font A: 12x24, Font B: 9x17, CHN: 24*24
1D barcode	CODE128, EAN128, ITF, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14	Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D bar code	QR code	QR code
Emulaion	TSPL	ESC/POS
Physical Features		
Dimension	190.3 x 133.8 x 127mm (D*W*H)	
Weight	0.71 kg	
Reliability		
Print head life	50 km	
Software		
Driver	Windows	Windows, Linux, Mac, Android
SDK	iOS/ Android/ Windows	
Power supply		
Input	100-240V 50/60H	
Output	DC 12V/3A	
Environmental Conditions		
Operation	0~45 °C Humidity: RH 10 ~ 80%	
Storage environment	-10 ~ 60°C Humidity: 10 ~ 90%	

ADPOS Retail Systems S.R.L. C.P. 030837 București
 Bd. Unirii nr 80, Bl J1, sc TR1, mezanin, sector 3
 GSM: 0 747 167 772 GSM: 0 747 167 778
 comenzi@adpos.ro

