













USB

1D & 2D

Android

10.1"

Megapixel

Touchscreen



SD









Dual





1/0 Ctrl I/O Ctrl







Features

Fully functioning CIT system.

With Octa-Core Cortex-A53 CPU up to 1.5GHz.

Easy to install and use anywhere.

Ideally suited for shelf mounting or on-counter usage in department stores, supermarkets, small grocery stores, pharmacy/cosmetic stores, tobacco kiosks and more.

Snappy reading performance.

Armed with Newland's EM2037-V4, 2D megapixel barcode scanner. The engine has a 20 degree scan angle for comfortable scanning of larger products. Also, available without a scanner.

Easily build applications.

The NQuire 1000 Manta is built on Android 7.1, allowing for easy development of custom applications, tailored to your needs.

Highly customizable with a broad range of features.

Dual band WiFi, Bluetooth embedded, front 5Mp camera, POE, speaker.

Variety of accessories.

The NQuire 1000 Manta offers a variety of optional accessories, including a Foldable desktop stand, VESA magnetic shelf stand and VESA wall mount. Additionally, optional modules for 4G, MSR, NFC and low frequency RFID help extend and tailor communication and data capture possibilities even further.

Modules can only be ordered pre-mounted to the connector on the left or right side.



Suggested industries











Sector

Tourism

NQuire 1000 Manta Technical specifications

Do	rfo	rm	an	00

renormance	
Image Sensor	CMOS 1280*800
Operating System	Android 7.1
Processor	RK3368, Octa-core Cortex-A53; up to 1.5 GHz , PowerVR G6110 GPU; up to 600MHZ
Memory RAM	2GB DDR3
Memory Flash	8GB Emmc
Illumination	Red LED(625±10 nm)
Aiming	Red LED(625±10 nm)
Minimal Print Contrast	25%
Scan Angle Roll	360°
Scan Angle Pitch	±55°
Scan Angle Skew	±55°
Field of View Horizontal	39°
Field of View Vertical	24°
Scan Modes	Sense Mode
Scan Rate	60 frames per second
Data Capture	

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar,	
	Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, GS1 Composite Code, Matrix 2	
	of 5, Code 11, Industrial 25, Standard 25, Plessey, MSI-Plessey.	
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Chinese Sensible Code, Aztec Code,	
	Maxicode, MicroPDF417.	

Physical

•	
Dimensions (mm)	252 × 184 × 33mm
Weight	615 g
Material	PC, ABS
VESA standard	Metal Fitting mounting screw holes: 75*75 mm
Display	10.1" WXGA, 1280*800 TFT LCD display
Touch Panel	10 points Capacitive Touch
Buttons	(Vol+ / Vol-) / (Up / Down) / Exit / Power switch
Interfaces	USB 2.0 port, type A port, GPIO port
Input Voltage	DC12V±5%
Power Supply Input	DC12V, 2A
Power Supply Output	AC100~240V, 50~60Hz
Sensors	G Sensor
Power over Ethernet	802.3af
Audio	1x 3.5mm Headset + MIC jack, 2x Integrated speakers 8Ω / 1.3W
Audio Jack	3.5mm earphone
Pogo Pin	2x POGO-PIN

+31 (0) 345 87 00 33 info@newland-id.com newland-id.com

Feel free to contact us or a partner near you visit newland-id.com/partners Specifications are subject to change without notice © Newland EMEA 2021, all rights reserved



NQuire 1000 Manta Technical specifications

Expansion Slot SD card

Camera Front: 5.0 MP camera

Video MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV

Environmental

Operating Temperature 0°C to 40°C (32°F to 104°F)

Storage Temperature -10°C to 55°C (14°F to 131°F)

Humidity 20% to 65% (40°C)

IP Rating IP54

Wireless

WLAN RADIO IEEE 802.11 b/g/n/ac (2.4G), IEEE 802.11 a/b/g/n/ac (5G)

WPAN RADIO Bluetooth 4.1

RFID Optional

Accessories

Standard Multi-pin, multi-plug AC/DC adapter with power cord, VESA 75 wall mount

Software

MDM (certified) Ndevor, SOTI, Airwatch

Terminal Emulation (compatible) IVANTI

Configuration Tools Ndevor

Certifications

Hardware CE, FCC, RoHS

Warranty

Standard 2 years

