
PE7 Series Label Printing Scales

General Specifications

- Display — 7" colour touch screen operator display(800x480)
  7" colour customer display (800x480)
- Capacities — 6kg~30kg
- Keyboard — 39keys (Membrane keyboard)
- Pan size — 280 x385mm
- Housing — ABS plastic
- Max. Divisions — 2 x 3,000e
- ADC update — ≤1/10 second
- Operate Temp — 0℃~+40℃
- Power — In put : AC 100~240V,50/60HZ
  Out put : DC (24V/5000mA)





T-Touch Central

- Standard TOS II embedded Operating System(1.2GHz)(Linux)
- CPU:A9 dual core;
- Memory:RAM:1G; Flash:1G
- Detachable pole can be adjusted to different enviroment
- Stainless steel pan
- PLU product and sale reports management
- 24 direct PLU key on the keypad
- Customer display allows for playing image advertisements
- Multi-language selection
- Multi-weighing units selection
- TTC Back Office Software Management allows to make product update, create customized print format, UI(operator interface) ,report management, data import&export,etc.
- Cassette type thermal printer, support label and receipt
  Max label width:60mm; Max print width:58mm; Max print length:180mm; printing speed:100mm/s
  Printer head life:150km; print resolution: 8dot/mm
- 2xUSB2.0; 2xRS232;1xRJ45;1xRJ11
- Optional WIFI application

PE7 Series Label Printing Scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
PE7-15-15K-MR	6kg/15kg	2g/5g	2x3,000e	11kg	CE;OIML;NTEP
PE7-15-30K-MR	15kg/30kg	5g/10g	2x3,000e	11kg	CE;OIML;NTEP

Options

Wifi

Dimensions(mm)

